



Sound Reinforcement and Lighting Rider – 4 Core Band, 3 Vocalists, 1 Sax

Front of House System (FOH)

- Midas M32 or Behringer X32 FOH board capable of 32 separate channels, dedicated to Liquid Blue. Mixing console to have 10 aux sends if no separate monitor board.
- High quality equalizers for Channels, Mains and Monitors.
- Amps, crossovers, and speakers for full range (bi or tri amp) live sound reinforcement, applicable to venue and audience size. Place subs on or near the dance floor.
- FOH sound and/or Monitor engineers to be provided by sound reinforcement company.

Monitors

- Nine on stage monitor wedges with adequate power and EQ.

Microphones and Stands

- Eight drum microphones and stands as needed for standard drum kit.
- One microphone for guitar amp.
- One microphone with stand for Sax.

Wireless Microphones

- Four professional quality, frequency agile handheld wireless microphones, with wireless mic clips and boom type mic stands.

Stage Power

- Two 20-amp, 120V circuits, placed at the back of the stage. Each to have a Quad Box with US outlets attached.
- One 120V Quad Box and US outlets, placed at the Keyboard position.

Lighting

- Intelligent DMX controlled upstage and downstage LED Stage Wash, 4+ Lekos focused for face lighting, and a minimum of 4 upstage moving head fixtures. Includes Light Tech operator.

Questions? Contact Michael Vangerov at michael@vantasticsound.com or 619.808.2009 (text only)
Skype: Michael Vangerov



Mixing Notes

- We want to have all line checks and a basic monitor mix complete by the scheduled time of the Full Band sound check and at that point just play full songs to dial in the monitors and FOH mix.
- The Keyboard Vocal mic volume should be as loud as the Lead Vocal mic in both the FOH and monitors. On some songs the lead vocal parts are sung from the keyboard.
- Each Vocalist will sing lead from their mic at some point during the performance.
- The Drummer has his own headphone monitor setup. If no wedge is available, he will need an aux mix sent to his monitor mixer which has a ¼" input.
- The Sax player generally only wants their instrument in their monitor.
- Once the mix has been dialed in, there should only be small changes made as needed during the show.
- When making requested changes to the FOH and monitors, please make subtle changes.

Questions? Contact Michael Vangerov at michael@vantasticsound.com or 619.808.2009 (text only)
Skype: Michael Vangerov